

# EnduroMat

EnduroMat is an general purpose smooth rubber used for a wide variety of applications, such as gaskets and waterproof seals, and is available in two different thicknesses, 3mm and 6mm.

## Features

- **Typical applications:** Ideal for waterproof seals and gaskets, workbench protective coverings, flooring, vehicle interiors and drawer and shelf liners.
- **Material:** 100% rubber.
- **Cleaning:** Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- **Sustainability:** REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- **Warranty:** Lifetime.



Suitable for indoor use



Code	Metric	Imperial	Thickness	Weight	Type	Colour
06-0339-1	140cm x 10m	5' x 33'	3mm	61kg	Roll	Black
06-0339-2	140cm x 10m	5' x 33'	6mm	116kg	Roll	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

# EnduroMat

## Technical Specification

Wear resistant: Excellent wear resistance to level 3, suitable for heavy footfall

Cut to length: Yes, the rubber can be cut to length

Cut to size: Yes, the rubber can be cut to bespoke sizes

Dry area: Yes

Wheeled area: Yes

Environment: Suitable for indoor use

Impact resistant: Yes

Product testing:

- Hardness Shore A  $\pm 5$  65° ISO 7619-1
- SG (g/cm<sup>2</sup>) 1.50 ISO 2781
- Tensile (N/mm<sup>2</sup>) 3 ISO 37
- Elongation % 250 ISO 37
- Compression % 43 ISO 37
- Tear Strength 10.5 ISO 34-1
- Abrasion mm<sup>3</sup> ISO 37

Sustainability:

- REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)
- Contributes to a cleaner environment by reducing the need to use cleaning chemicals

Temperature resistance: -20°C to +70°C

Cleaning: Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended